



NEW!!
TSERIES

Clarity. Precision. Honesty. Detail.

AX SERIES

S SERIES

SUB WOOFER

MAIN MONITORS

S6X Main Monitor



Specification

- German handmade precision X-ART tweeter
- 2 x German handmade precision X-ART mid-range driver
- 2 x 7.5" Mid-range Woofers, 2 x 12" Woofers,
- Inputs: XLR
- Amplifier Power: Tweeter 250 W [RMS], Mid-range 2 x 250 W [RMS], Mid-range Woofer 2 x 250 W [RMS], Woofers 2 x 500 W [RMS]
- Frequency Response: 23 Hz – 50 kHz
- Max. Peak SPL per Pair: 133 dB
- 3 Parametric EQs

S7A Mk2 Main Monitor



Specification

- German handmade precision X-ART tweeter
- 2 x German handmade precision X-ART mid-range driver
- 2 x 9" Mid-range Woofers, 2 x 15" Woofer, Inputs: XLR
- Amplifier Power: Tweeter 250 W [RMS], Mid-range 2 x 250 W [RMS], Mid-range Woofers 1 x 250 W [RMS],
- 1 x 500 W [RMS], Woofers 1 x 500 W [RMS], 1 x 1000 W [RMS]
- Frequency Response: 20 Hz – 50 kHz
- Max. Peak SPL per Pair: 138 dB
- 3 Parametric EQs

SUBWOOFER

Lower bass - not louder bass

SUB7 Subwoofer



Specification

- 7" Woofer
- Amplifier Power: 140 W [RMS]
- Controls: Volume, Crossover Frequency, Phase
- Frequency Response: 32 Hz – 150 Hz
- Crossover Frequencies: 50 Hz – 150 Hz
- Input: XLR & RCA
- Max. Peak SPL: 107 dB & Remote Control

SUB8 Subwoofer



Specification

- 8.5" Woofer
- Amplifier Power: 160 W [RMS]
- Controls: Volume, Crossover Frequency, Phase
- Frequency Response: 28 Hz – 150 Hz
- Crossover Frequencies: 50 Hz – 150 Hz
- Input: XLR & RCA
- Max. Peak SPL: 110 dB & Remote Control

SUB10 Mk2 Subwoofer



Specification

- 10" Woofer
- Amplifier Power: 200 W [RMS]
- Controls: Volume, Crossover Frequency, Phase
- Frequency Response: 25 Hz – 150 Hz
- Crossover Frequencies: 50 Hz – 150 Hz
- Input: XLR & RCA
- Max. Peak SPL: 113 dB
- Remote Control

SUB15 Subwoofer



Specification

- 15" Woofer
- Amplifier Power: 1000 W [RMS]
- Controls: Volume, Crossover Frequency, Phase
- Frequency Response: 20 Hz – 150 Hz
- Crossover Frequencies: 50 Hz – 150 Hz
- Input: XLR & RCA
- Max. Peak SPL: 120 dB

SUB12 Subwoofer



Specification

- 12" Woofer
- Amplifier Power: 200 W [RMS]
- Controls: Volume, Crossover Frequency, Phase
- Frequency Response: 22 Hz – 150 Hz
- Crossover Frequencies: 50 Hz – 150 Hz
- Input: XLR & RCA
- Max. Peak SPL: 115 dB

SUB2100 Subwoofer



Specification

- 21.5" Woofer
- Amplifier Power: 1000 W [RMS]
- Controls: Volume, Crossover Frequency, Phase
- Frequency Response: 18 Hz – 150 Hz
- Crossover Frequencies: 50 Hz – 150 Hz
- Input: XLR & RCA
- Max. Peak SPL: 128 dB

S3H Midfield Monitor



PROFESSIONAL AUDIO
Rating: Excellent

PROFESSIONAL AUDIO
Editors' Choice

Specification

- German handmade precision S-ART tweeter
- HPS Waveguide
- 4" DCH Mid-range
- 2 x 7" ELE Woofer
- Inputs: XLR, AES3
- Amplifier Power: Tweeter 50 W [RMS], Mid-range 300 W [RMS], Woofer 2 x 500 W [RMS]
- Frequency Response: 32 Hz – 50 kHz
- Max. Peak SPL per Pair: 126 dB
- DSP with High Shelf and Low Shelf filters + 6 parametric EQs

S5V Main Monitor



Specification

- German handmade precision S-ART tweeter
- HPS and MPS Waveguide
- 4" DCH Mid-range
- 12" ELE Woofer
- Inputs: XLR, AES3
- Amplifier Power: Tweeter 100 W [RMS], Mid-range 300 W [RMS], Woofer 700 W [RMS]
- Frequency Response: 26 Hz – 50 kHz
- Max. Peak SPL per Pair: 128 dB
- DSP with High Shelf and Low Shelf filters + 6 parametric EQs

S5H Main Monitor



Specification

- German handmade precision S-ART tweeter
- HPS and MPS Waveguide
- 4" DCH Mid-range
- 2 x 10" ELE Woofer
- Inputs: XLR, AES3
- Amplifier Power: Tweeter 100 W [RMS], Mid-range 300 W [RMS], Woofer 2 x 700 W [RMS]
- Frequency Response: 24 Hz – 50 kHz
- Max. Peak SPL per Pair at 1m: 131 dB
- DSP with High Shelf and Low Shelf filters + 6 parametric EQs

T SERIES

Clarity. Precision. Honesty. Detail.



T5V Nearfield Monitor



- Specification**
- U-ART 1.9" Accelerated Ribbon Tweeter with HPS Waveguide
 - Polypropylene 5" woofer and rear-firing bass-reflex port
 - Cumulated Amp. Power RMS: 70 W
 - Frequency Response: 45 Hz - 25 kHz
 - Max. SPL Per Pair at 1 m: ≥ 106 dB

T7V Nearfield Monitor



- Specification**
- U-ART 1.9" Accelerated Ribbon Tweeter with HPS Waveguide
 - Polypropylene 7" woofer and rear-firing bass-reflex port
 - Cumulated Amp. Power RMS: 70 W
 - Frequency Response: 39 Hz - 25 kHz
 - Max. SPL Per Pair at 1 m: ≥ 110 dB

AX SERIES

Near-/Midfield Monitors



A3X Nearfield Monitor



- Specification**
- German handmade precision X-ART tweeter
 - 4.5" Woofer
 - On/off switch and Volume Control on the front panel
 - Inputs: XLR & RCA
 - Amplifier Power: Tweeter 25 W [RMS], Woofer 25 W [RMS]
 - Frequency Response: 60 Hz – 50 kHz
 - Max. Peak SPL per Pair: 106 dB
 - Stereo Link
 - Tweeter Gain
 - Optional: Desktop Stands / Wallmount

A5X Nearfield Monitor




- Specification**
- German handmade precision X-ART tweeter
 - 5.5" Woofer
 - On/off switch and Volume Control on the front panel
 - Inputs: XLR & RCA
 - Amplifier Power: Tweeter 50 W [RMS], Woofer 50 W [RMS]
 - Frequency Response: 50 Hz – 50 kHz
 - Max. Peak SPL per Pair: 110 dB
 - Stereo Link
 - Tweeter Gain
 - Low and High Shelf filters
 - Optional: Desktop Stands / Wallmount

A7X Nearfield Monitor



- Specification**
- German handmade precision X-ART tweeter
 - 7" Woofer
 - On/off switch and Volume Control on the front panel
 - Inputs: XLR & RCA
 - Amplifier Power: Tweeter 50 W [RMS], Woofer 100 W [RMS]
 - Frequency Response: 42 Hz – 50 kHz
 - Max. Peak SPL per Pair: 114 dB
 - Tweeter Gain
 - Low and High Shelf filters



A8X Nearfield Monitor



- Specification**
- German handmade precision X-ART tweeter
 - 8.5" Woofer
 - On/off switch and Volume Control on the front panel
 - Inputs: XLR & RCA
 - Amplifier Power: Tweeter 50 W [RMS], Woofer 150 W [RMS]
 - Frequency Response: 38 Hz – 50 kHz
 - Max. Peak SPL per Pair: 120 dB
 - Tweeter Gain
 - Low and High Shelf filters



A77X Nearfield Monitor



- Specification**
- German handmade precision X-ART tweeter
 - 2 x 7" Woofer
 - On/off switch and Volume Control on the front panel
 - Inputs: XLR & RCA
 - Amplifier Power: Tweeter 50 W [RMS], Woofer 2 x 100 W [RMS]
 - Frequency Response: 38 Hz – 50 kHz
 - Max. Peak SPL per Pair: 122 dB
 - Tweeter Gain
 - Low and High Shelf filters



S SERIES



S2V Nearfield Monitor



- Specification**
- German handmade precision S-ART tweeter
 - HPS Waveguide
 - 7" ELE Woofer
 - Inputs: XLR, AES3
 - Amplifier Power: Tweeter: 50 W [RMS], Woofer 300 W [RMS]
 - Frequency Response: 35 Hz – 50 kHz
 - Max. Peak SPL per Pair: 120 dB
 - DSP with High Shelf and Low Shelf filters + 6 parametric EQs

S3V Midfield Monitor



- Specification**
- German handmade precision S-ART tweeter
 - HPS Waveguide
 - 4" DCH Mid-range
 - 9" ELE Woofer
 - Inputs: XLR, AES3
 - Amplifier Power: Tweeter 50 W [RMS], Mid-range 300 W [RMS], Woofer 500 W [RMS]
 - Frequency Response: 32 Hz – 50 kHz
 - Max. Peak SPL per Pair: 124 dB
 - DSP with High Shelf and Low Shelf filters + 6 parametric EQs