



C01+

USB Studio Condenser Microphone Bundle
Large diaphragm condenser microphone suitable for Vocal & Instruments



Features	USB
Type	34mm dia. Pressure Gradient Transducer
Response Type	Cardioid
Frequency Response	20Hz to 20kHz
Sensitivity	-34dB±2dB (0 dB = 1V/Pa)
Self Noise	16dBA
Maximum SPL	132dB (1 kHz)
S/N Ratio	78dB (A- weighted)
Impedance	150 ohms
Power	USB power
Resolution	16 bit / 48kHz

- C01+ ia a new revolutionary microphone for world class vocal
- cardioid
- USB

In the box:

- ★ Microphone
- ★ Windscreen
- ★ Pop Filter
- ★ Shock Mount
- ★ Scissor Stand
- ★ 3M Cable
- ★ One year Warranty



C01+

Studio Condenser Microphone

Large diaphragm condenser microphone suitable for Vocal & Instruments



Features	XLR
Type	34mm dia. Pressure Gradient Transduc
Polar Pattern	Cardioid
Frequency Response	20Hz to 20kHz
Sensitivity	-34dB±2dB (0 dB = 1V/Pa)
Self Noise	16dBA
Maximum SPL	132dB (1 kHz)
S/N Ratio	78dB (A- weighted)
Impedance	150 ohms
Power	Via 48 V phantom supply
Output	XLR

- C01+ ia a new revolutionary microphone for world class vocal
- cardioid
- XLR

In the box:

- ★ Microphone
- ★ Windscreen
- ★ Stand Mount
- ★ Mini Tripod Stand
- ★ 3M XLR Cable
- ★ Plastic Box
- ★ One Year Warranty



C01+

XLR Studio Condenser Microphone Bundle

Large diaphragm condenser microphone suitable for Vocal & Instruments



- C01+ ia a new revolutionary microphone for world class vocal
- cardioid
- XLR

In the box:

- ★ Microphone
- ★ Pop Filter
- ★ Shock Mount
- ★ Scissor Stand
- ★ 3M XLR Cable
- ★ One year Warranty

Features	XLR
Type	34mm dia. Pressure Gradient Transduc
Polar Pattern	Cardioid
Frequency Response	20Hz to 20kHz
Sensitivity	-34dB±2dB (0 dB = 1V/Pa)
Self Noise	16dBA
Maximum SPL	132dB (1 kHz)
S/N Ratio	78dB (A- weighted)
Impedance	150 ohms
Power	Via 48 V phantom supply
Output	XLR



HA400MKII

Headphone Amp Four 1/4" Stereo Outputs

Specification:

- 4 channel headphone amplifier
- Input connector: 1/4", TRS
- Input Impedance: 1000KΩ(unbalance)
- Max output level: +22dB
- Output connector: 6.35mm stereo
- Output Impedance: minimum 10Ω each channel
- Max gain: 20-dB each channel
- Signal to Noise Ratio:>98dB
- Supply: 12V DC adaptor



HP-100

Monitor Headphones

Built For Quality DJ & Studio Performance



Type:
Stereo Over-Ear Design
Driver Diameter:
50mm
Impedance:
32 ohm
Body Construction:
Faux Leather-wrapped
Metal Headband

Frequency Response:
15Hz-25KHz
Sensitivity (S.P.L):
94dB± 3dB
Cord Length:
3 Meter & Tangle Resistant
Plug (Gold Plated):
3.5mm & 6.3mm (1/4") Adaptor