

UBER SERIES



UBER PA
50-watt Portable Rechargeable
Bluetooth® Pa System

- Portable self-powered PA system
- 50 watts (peak) drives high-quality 6.5-inch woofer, 2-inch tweeter
- Two Line/Mic channels with XLR/1/4" (6.35 mm) combo inputs
- Streams music wirelessly from any Bluetooth-enabled device
- NFC pairing and 1/8"
- Master Volume, Line Out and battery level indicator
- Built-in rechargeable battery delivers up to 50 hours continuous use
- USB charging port for phone, tablet or other device
- Top panel storage tray for smartphones, keys, guitar picks, and more



UBER FX
100-watt Portable Rechargeable
Bluetooth® PA System

- 100 watts (peak) drives high-quality 8-inch woofer, 3-inch tweeter
- Two Line/Mic channels with XLR/1/4-inch (6.35 mm) combo inputs, independent Volume, independent 2-Band EQ, independent Effects Level Controls and 15 built-in Alesis digital effects
- NFC pairing and 1/8-inch (3.5 mm) stereo aux channels
- Built-in rechargeable battery delivers up to 45 hours continuous use
- USB charging port for phone, tablet or other device
- Top panel storage tray for smartphones, keys, guitar picks, and more
- Telescoping handle with built-in wheels for easy transport



UBER LT
50-watt Portable Rechargeable
Bluetooth® PA System

- 50 watts (peak) drives high-quality 6.5-inch woofer, 2-inch tweeter
- Two Line/Mic channels with XLR/1/4" combo inputs
- NFC pairing and 1/8"
- Master Volume, Line Out and battery level indicator
- Built-in rechargeable battery delivers up to 35 hours continuous use
- USB charging port for phone, tablet or other device
- Top panel storage tray for smartphones, keys, guitar picks, and more
- Rugged design with built-in back handle for easy transport

HIGHLIGHTED PRODUCTS



TROUPER
Compact High-Performance PA System

- (2) XLR+1/4-inch combo inputs + stereo RCA and 1/8-inch inputs. Connect microphones, instruments, DJ mixers, controllers and more
- Bi-amplified design with (3) 6.5-inch low/mid woofers and a 1-inch high-frequency tweeter
- XLR link output for use with additional loudspeakers and subwoofers
- Integrated 3-channel professional audio mixer with volume and 2-band EQ on each channel
- Bluetooth Link-Stream a stereo signal to separate speakers—no cables required

ZMX SERIES



ZMX 52
5-Channel Compact Mixer

- Six total inputs with a phantom powered XLR jack on channel 1
- 1/4" Main, Tape, Headphone & Aux outputs for flexible signal routing
- Mic input channel with gold plated XLR and balanced line input
- Two stereo input channels with balanced TRS jack
- Ultra-low-noise discrete mic preamp with Phantom power
- Balanced inputs for highest signal integrity and low-noise operation
- Warm, natural two-band EQ on mono channel
- 2-Track inputs w/assignable bus: main mix or headphone out
- Highly accurate four-segment bar graph meters
- Aux inputs/outputs for external audio source integration
- Peak LEDs on each channel



ZMX 862
6-Channel Compact Mixer

- 12 total inputs including XLR jacks w/ phantom power on ch. 1 & 2
- Expanded channel count perfect for small groups or sub-mixes
- High headroom circuitry offering extra dynamic range
- Ultra-low-noise discrete mic preamps
- 2 aux sends per channel for external effects and monitoring
- 3-band EQ on each channel
- Two stereo input channels with balanced TRS jacks
- Aux inputs/outputs for external audio source integration
- Switchable phantom power



ZMX 122 FX
8-channel Compact
Mixer with Effects

- 16 total inputs including XLR jacks w/ phantom power on ch. 1-4
- 4 mic input channels with gold-plated XLR and balanced line inputs
- Two stereo input channels with balanced TRS jacks
- 3-band EQ on each channel
- 2 aux sends per channel for external effects and monitoring
- 2-bus design with Main and Control Room 1/4" stereo outputs
- Aux inputs/outputs for external audio source integration
- On-board Alesis digital effects with 256 variations
- Switchable phantom power

LIVE SERIES

Live Mixers With Dynamics Control,
I/o And 100 High-quality Alesis DSP Effects &
Headphone Out With Independent Level Control

LIVE 802

Professional 8-Channel/2-bus Mixer



- 5 XLR inputs with DNA™ microphone preamps
- Dynamic compression (channels 1-2)
- 3-band EQ plus 2 aux sends per channel
- 60mm faders with mute switch and LED
- USB audio connectivity with level control
- Balanced XLR, balanced/unbalanced 1/4" outputs
- 9-band graphic EQ for main or monitor outputs

LIVE 1202

Professional 12-Channel/2-bus Mixer



- 7 XLR inputs with high- DNA™ mic preamps
- Dynamic compression (Channels 1-4)
- 3-band EQ plus 2 aux sends per channel
- 60mm faders with mute switch and LED meters
- USB audio connectivity with level control
- Balanced XLR, balanced/unbalanced 1/4" outputs
- 9-band graphic EQ for main or monitor outputs



LIVE 1604
Professional
16-Channel/4-bus Mixer

- 10 XLR inputs with DNA(TM) microphone preamps
- Dynamic compression (channels 1-6)
- 3-band EQ with sweepable mids
- 4 aux sends; pre/post switching on sends 1+2
- 60mm faders with mute and PFL/AFL solo functions
- USB audio connectivity with level control
- Balanced XLR, balanced/unbalanced 1/4" outputs
- Switchable phantom power



LIVE 2404
Professional 24-Channel / 4-bus Mixer

- 18 XLR inputs with DNA(TM) microphone preamps
- Dynamic compression (channels 1-8)
- 3-band EQ with sweepable mids
- 4 aux sends; pre/post switching on sends 1+2
- 60mm faders with mute and PFL/AFL solo functions
- USB audio connectivity with level control
- Balanced XLR, balanced/unbalanced 1/4" outputs
- Switchable Phantom Power

ALTO
PROFESSIONAL

DESIGNED AND TUNED IN THE USA



PROFESSIONAL DESIGN.
ELEGANT STYLE.
SOUND INVESTMENT.

TX2 SERIES
LOUDSPEAKERS

ALTOPROFESSIONAL.COM

TriMac

Trimac Products Private Limited

AUTHORISED DISTRIBUTOR

D-40, DSIIDC Packaging Complex, Kirti Nagar, Delhi - 110015,
www.trimacppl.com | info@trimacppl.com

TX2 SERIES

- The newly designed horn delivers greater coverage 90° H x 60° V
- The full grille delivers style and provides protection for your investment.
- 1-inch (25.4 mm) titanium diaphragm HF compression driver
- Lightweight, portable design for main or wedge monitor operation
- Standard speaker pole socket
- Bi-amplified design with precision active crossover and EQ



TX208

300-watt 8-inch 2-way
Powered Loudspeaker

- 300 Watts peak, (150 Watts continuous Class D power)
- The full grille delivers style and provides protection for your investment.
- 8-inch (203 mm) LF driver, 1.5-inch (38.1 mm) voice coil
- Balanced XLR Mic/Line input, Link Output and Volume control



TX210

300-watt 10-inch 2-way
Powered Loudspeaker

- 300 Watts peak, (150 Watts continuous Class D power)
- 10-inch (254 mm) LF driver, 1.5-inch (38.1 mm) voice coil
- Balanced XLR Mic/Line input, Link Output and Volume control



TX212

600-watt 12-inch 2-way
Powered Loudspeaker

- 600 Watts peak, (300 Watts continuous Class D power)
- 12-inch (305 mm) LF driver, 2-inch (50.8 mm) voice coil
- Balanced XLR/TRS with selectable Mic/Line input. XLR Link Output, Contour EQ switch and Ground-Lift switch



TX215

600-watt 15-inch 2-way
Powered Loudspeaker

- 600 Watts peak, 300 Watts continuous Class D power
- 15-inch (381 mm) LF driver, 2-inch (50.8 mm) voice coil
- Balanced XLR/TRS with selectable Mic/Line input. XLR Link Output, Contour EQ switch and Ground-Lift switch




TX212S

Rugged, Dynamic 12-inch Subwoofer
Featuring 900 Watts Of Explosive Power

- 900 watts of peak power output
- High-efficiency Class D amplifier
- Transducer: 12-inch with 2.5-inch high-temperature voice coil
- (2) XLR+1/4-inch combo inputs + (2) balanced XLR line outputs
- XLR outputs, with six discreet DSP output modes for ideal matching with companion full-range speaker
- Polarity Reverse switch and Extended LF switch for increased EQ control
- Electronic clip, thermal and transducer overdrive protection
- Rugged, internally-braced front-ported MDF cabinet with integrated 36mm pole socket
- Rugged, mar-resistant splatter-spray finish always looks good, even with heavy use

TRUESONIC 3 SERIES

- 2000 W peak (1300 LF + 700 HF) 1000 W continuous RMS (650 LF + 350 HF)
- HF Driver: 1.4-inch (35 mm) neodymium magnet HF driver with precision waveguide
- High quality, lightweight, cabinet design for easy transport, set up and installation
- Pole-mountable, wedge monitor, bracket installation or flown application with integral M6 suspension points
- Integrated 2-channel mixer with dual XLR 1/4-inch combo mic/line inputs, independent level controls, XLR Link output, Contour EQ switch and Ground-Lift switch
- Custom-engineered high-efficiency class D amplifiers with passive cooling design – no fan means the speaker runs cleaner, quieter and has greater long-term reliability
- Design Origin: Designed and tuned in the USA



TS308

2000-watt 8-inch 2-way
Powered Loudspeaker


- 2000 W peak (1300 LF + 700 HF) 1000 W continuous RMS (650 LF + 350 HF)
- 8-inch (203 mm) LF driver, 2.5-inch (65 mm) high-temperature voice coil
- HF Driver: 1.4-inch (35 mm) neodymium magnet HF driver with precision waveguide
- Pole-mountable, wedge monitor, bracket installation or flown application with integral M6 suspension points



TS310

2000-watt 10-inch 2-way
Powered Loudspeaker


- 2000 W peak (1300 LF + 700 HF) 1000 W continuous RMS (650 LF + 350 HF)
- 10-inch (254 mm) LF driver, 2.5-inch (65 mm) high-temperature voice coil
- HF Driver: 1.4-inch (35 mm) neodymium magnet HF driver with precision waveguide
- Pole-mountable, wedge monitor, bracket installation or flown application with integral M0 suspension points



TS312

2000-watt 12-inch 2-way Powered Loudspeaker

- 2000 W peak (1300 LF + 700 HF) 1000 W continuous RMS (650 LF + 350 HF)
- 12-inch (305 mm) LF driver, 3-inch (76 mm) high-temperature voice coil
- 1.4-inch (35 mm) neodymium magnet HF driver with precision wave guide
- High quality, lightweight, cabinet design for easy transport, set up and installation
- Pole-mountable, wedge monitor, bracket installation or flown application with integral M10 suspension points



TS315

2000-watt 15-inch 2-way Powered Loudspeaker

- 2000 W peak (1300 LF + 700 HF) 1000 W continuous RMS (650 LF + 350 HF)
- 15-inch (381 mm) LF driver, 3-inch (76 mm) high-temperature voice coil
- 1.4-inch (35 mm) neodymium magnet HF driver with precision wave guide
- Pole-mountable, wedge monitor, bracket installation or flown application with integral M10 suspension points

TS3S SERIES



TS312S

Truesonic 3 12-inch
Powered Subwoofer
Integrated 35mm pole socket


- Driver: 12-inch with high-temperature, long-throw voice coil
- Amplifier: 1000W continuous, 2000W peak Class D power
- XLR outputs, with six discreet output modes for ideal matching with companion speaker
- Extended LF switch for increased EQ control
- Electronic clip, thermal and transducer overdrive protection



TS315S

Truesonic 3 15-inch
Powered Subwoofer
Integrated 35mm pole socket

- Driver: 15-inch with high-temperature, long-throw voice coil
- Amplifier: 1000W continuous, 2000W peak Class D power
- XLR outputs, with six discreet output modes for ideal matching with companion speaker
- Extended LF switch for increased EQ control
- Electronic clip, thermal and transducer overdrive protection



TS318S

Truesonic 3 18-inch
Powered Subwoofer
Integrated 35mm pole socket

- Driver: 18-inch with high-temperature, long-throw voice coil
- Amplifier: 1000W continuous, 2000W peak Class D power
- XLR outputs, with six discreet output modes for ideal matching with companion speaker
- Extended LF switch for increased EQ control
- Electronic clip, thermal and transducer overdrive protection

TRUESONIC 2 SUBWOOFERS



TS212S

1250-watt 12"
Powered Subwoofer



- 1250 watts of peak power output
- 12-inch high-excursion woofer
- (2) XLR+1/4-inch combo inputs + (2) balanced XLR line outputs
- Integrated 35mm speaker pole socket
- Polarity Reverse, Full-Range Output and Extended LF controls




TS215S

1250-watt 15"
Powered Subwoofer



- 1250 watts of peak power output
- 15-inch high-excursion woofer
- (2) XLR+1/4-inch combo inputs + (2) balanced XLR line outputs
- Integrated 35mm speaker pole socket
- Polarity Reverse, Full-Range Output and Extended LF controls



TS218S

1250-watt 18"
Powered Subwoofer



- 1250 watts of peak power output
- 18-inch high-excursion woofer
- (2) XLR+1/4-inch combo inputs + (2) balanced XLR line outputs
- Integrated 35mm speaker pole socket
- Polarity Reverse, Full-Range Output and Extended LF controls