


HAWK®
TOTAL MUSIC SOLUTION

www.hawkpro.in

HAWK®
TOTAL MUSIC SOLUTION

NEW!
Impulse
SERIES
ACTIVE SPEAKERS



Unleash
the
Beat.

2 YEAR MANUFACTURING WARRANTY AND

1 YEAR EXTENDED WARRANTY UPON REGISTRATION.

MICROPHONE



LEO

Premium Quality Condenser Microphone

*Capsule size: 34mm
Capsule Type: Condenser
Capsule Diaphragm: Gold
Frequency Response: 20Hz-20kHz
Sensitivity: -32dB±2dB (at 1kHz 0dB=1V/Pa)
Max SPL: 130dB SPL (at 1kHz≤1% T.H.D)
S/N: ≤12dB A
Directivity: Cardioid
Power Dupplier: 48V Phantom Power
AC: 3.2 mA*



HM01

Premium Quality Dynamic Microphone

*Capsule: Dynamic
Polar Pattern: Cardioid
Frequency Response: 50Hz-16kHz
Sensitivity: -55dB±2dBV/Pa (0dB=1V/Pa at 1kHz)
Output Impedance: 140Ω±30% at 1kHz
Max. Input SPL: 135dB SPL*



HM05

Premium Quality Dynamic Microphone

*Capsule: Dynamic
Polar Pattern: Ultra - Cardioid
Frequency Response: 60Hz-13kHz
Sensitivity: -55.3(±3) dB (at 1kHz) (dB=1V/Pa)
Output Impedance: 600Ω±30% at 1kHz
Max. Input SPL: 135dB SPL*



HM10

Premium Quality Dynamic Microphone

*Capsule: Dynamic
Polar Pattern: Cardioid
Frequency Response: 50Hz-16kHz
Sensitivity: -75dB±3dBV/Pa (0dB=1V/Pa at 1kHz)
Output Impedance: 500Ω±30% at 1kHz
Max. Input SPL: 135dB*

MICROPHONE



HM50
Premium Quality
Dynamic Microphone

Capsule: Dynamic
Polar Pattern: Cardioid
Frequency Response: 50Hz-53kHz
Sensitivity: -75dB±3dBV/Pa (0dB=1V/Pa at 1kHz)
Output Impedance: 600Ω±30% at 1kHz



HM57
Dynamic Instrument
Microphone

Polar Pattern: Cardioid
Frequency Response: 50Hz-16kHz
Sensitivity: -56dB±3dBV/Pa (0dB=1V/Pa at 1kHz)
Output Impedance: 19Ω±20% at 1kHz



ELARA
Studio Condenser
Microphone

Element: Ø34mm gold plated diaphragm
Polar Pattern: Cardioid
Frequency Response: 20Hz-20kHz
Sensitivity: -34dB±2dB (0dB=1V/Pa at 1kHz)
Output Impedance: 200Ω±30% (at 1kHz)
Overload Impedance: ≥1000Ω
Equivalent Noise Level: 15dB A
Max SPL: 135dB(at 1kHz≤1%T.H.D)
S/N ratio: 79dB
Voltage: 48V phantom Power
Current Consumption: 3.2mA



ATHENA
Studio Condenser
Microphone

Capsule: Ø34mm gold plated diaphragm
Frequency Response: 20Hz-20kHz
Sensitivity: -31dB±2dB(at 1kHz 0dB=1V/Pa)
Max SPL: 135dB SPL(at 1kHz≤1%T.H.D)
S/N ratio: ≥72dB
Polar Pattern: Cardioid
Power Analog reg.: 48V Phantom Power
Output Connectivity: 3-Pin XLR
Current Consumption: 4.8mA

MICROPHONE



WSH-1000
Wireless Microphone System

*Carrier frequency: 640-690MHz
Frequency Stability: ±0.005%
Frequency : selectable with 100Freq.
Modulation mode: FM
Maximum Deviation: ±20KHz
Audio Frequency Response: 50Hz-18KHz
S/N ratio: >80dB
Audio Dynamic Range: >80dB
T.H.D.:<0.8%
Cover Range: 50-80M(in open space)*



WDH-2000
Wireless Microphone System

*Carrier frequency: 640-690MHz
Frequency Stability: ±0.005%
Frequency : selectable with 200Freq.
Modulation mode: FM
Maximum Deviation: ±20KHz
Audio Frequency Response: 50Hz-18KHz
S/N ratio: >80dB
Audio Dynamic Range: >80dB
T.H.D.:<0.8%
Cover Range: 50-80M(in open space)*



WDL-3000
Wireless Microphone System

*Carrier frequency: 640-690MHz
Frequency Stability: ±0.005%
Frequency : selectable with 200Freq.
Modulation mode: FM
Maximum Deviation: ±20KHz
Audio Frequency Response: 50Hz-18KHz
S/N ratio: >80dB
Audio Dynamic Range: >80dB
T.H.D.:<0.8%
Cover Range: 50-80M(in open space)*



WDHS-4000
Wireless Microphone System

*Carrier frequency: 640-690MHz
Frequency Stability: ±0.005%
Frequency : selectable with 200Freq.
Modulation mode: FM
Maximum Deviation: ±20KHz
Audio Frequency Response: 50Hz-18KHz
S/N ratio: >80dB
Audio Dynamic Range: >80dB
T.H.D.:<0.8%
Cover Range: 50-80M(in open space)*

SPEAKERS



VIBE 12
12" Active Speaker

System: 2-way full range
Woofers: 12", 600Z magnet
Tweeter: 44mm PEN.Diap.Driver
Peak Power: 2000Watts
Impedance: 40OHM
Frequency Range: 40Hz~18KHz

Sensitivity: 102dB(+/-2dB)
Connectivity: XLR/COMBO/Bluetooth
Mic Input Level: <5mV
Line Input/ Output Level: 250mV
Package size: 445X415X690MM
DSP Mode: 4 Presets



VIBE 15
15" Active Speaker

System: 2-way full range
Woofers: 15", 800Z magnet
Tweeter: 44mm PEN.Diap.Driver
Peak Power: 2000Watts
Impedance: 40OHM
Frequency Range: 40Hz~18KHz

Sensitivity: 108dB(+/-2dB)
Connectivity: XLR/COMBO/Bluetooth
Mic Input Level: <5mV
Line Input/ Output Level: 250mV
Package size: 485X480X785MM
DSP Mode: 4 Presets



VIBE 115A
15" Active Subwoofer

System: 15 Subwoofer
Woofers: 15", 800Z magnet
Peak Power: 2200Watts
Impedance: 80HM
Frequency Range: 35Hz~150Hz

Sensitivity: 126dB(+/-2dB)
Connector: XLR/COMBO
Line Input / Output Level: 250mV
Package size: 655X540X670MM



VIBE 118A
18" Active Subwoofer

System: 18 Subwoofer
Woofers: 18", 800Z magnet
Peak Power: 2600Watts
Impedance: 80HM
Frequency Range: 30Hz~130KHz

Sensitivity: 132dB(+/-2dB)
Connector: XLR/COMBO
Line Input / Output Level: 250mV
Package size: 715X595X740MM



VIBE MINI8BT
All-in-One Battery-Powered
Portable PA with
Professional-Grade Mixer

System: Bidirectional
Woofers: 8", 400Z magnet
Tweeter: 25mm titanium film. conductor
Maximum Power: 1800Watts
Impedance: 8ohms
Frequency Range: 40Hz~18KHz
Consider: 98dB(+/-2dB)
Connectivity: XLR/COMBO/Bluetooth/RCA/Aux
Mic Input Level: <5mV
Line Input/ Output Level: 250volts
Power Supply: 220volts

SPEAKERS



IMPULSE 8
400W
8" ACTIVE SPEAKER

Peak Power: 400W
Impedance: 8OHM
Woofer: 8" 40OZ magnet
Tweeter: 34mm Ti. Diap. Driver
Frequency Range: 90Hz~18KHz
Sensitivity: 121dB(+/-2dB)
DSP Mode: 4 Presets



IMPULSE 10
500W
10" ACTIVE SPEAKER

Peak Power: 500W
Impedance: 8OHM
Woofer: 10" 40OZ magnet
Tweeter: 34mm Ti. Diap. Driver
Frequency Range: 80Hz~18KHz
Sensitivity: 125dB(+/-2dB)
DSP Mode: 4 Presets



IMPULSE 12
800W
12" ACTIVE SPEAKER


Peak Power: 800W
Impedance: 4OHM
Woofer: 12" 60OZ magnet
Tweeter: 44mm PEN. Diap. Driver
Frequency Range: 20Hz~18KHz
Sensitivity: 135dB(+/-2dB)
DSP Mode: 4 Presets



IMPULSE 15
1000W
15" ACTIVE SPEAKER

Peak Power: 1000W
Impedance: 4OHM
Woofer: 15" 60OZ magnet
Tweeter: 44mm PEN. Diap. Driver
Frequency Range: 20Hz~18KHz
Sensitivity: 145dB(+/-2dB)
DSP Mode: 4 Presets

SPEAKERS



PULSE 12

1000 Watts
12" Active Speaker

Type: Two way Bi-Amp

Frequency Response: 55Hz-20kHz

Sensitivity(1m/1w): 93dB

Impedance: 4ohms

Woofer: 1X12" 65mm 50OZ

Driver: 1.75" Titanium

SPL: 123dB

Bluetooth Module: Yes

DSP: 4 Presets

Protections:


Over Temp;OverLoad;DC Protect;Over

Voltage;Low Voltage;Soft start.

Crossover: 2.0Khz

Dimension(WxHxD): 435x405x680mm

Weight: 19kg



PULSE 15

1000 Watts
15" Active Speaker

Type: Two way Bi-Amp

Frequency Response: 50Hz-20kHz

Sensitivity(1m/1w): 93dB

Impedance: 4ohms

Woofer: 1X15" 75mm 60OZ

Driver: 1.75" Titanium

SPL: 126dB

Bluetooth Module: Yes

DSP: 4 Presets

Protections:

Over Temp;OverLoad;DC Protect;Over

Voltage;Low Voltage;Soft start.

Crossover: 2.0Khz

Dimension(WxHxD): 475x475x775mm

Weight: 24kg



PULSE 15 SUB

1600W
15" Active Subwoofer

Type: 15" Active Sub Woofer

Frequency Response: 30Hz-200kHz

Sensitivity(1m/1w): 96.5dB

Impedance: 4ohms

Woofer: 15" 100mm 100OZ

SPL: 125dB

DSP: 48KHz Sampling Frequency 24 Bit

Amp Type: Class D

Amp Power: 800RMS

Peak Power: 1600W

Dimension(WxHxD): 610x540x620mm

Weight: 36kg



PULSE 18 SUB

1600W
18" Active Subwoofer

Type: 18" Active Sub Woofer

Frequency Response: 30Hz-200kHz

Sensitivity(1m/1w): 96.5dB

Impedance: 4ohms

Woofer: 18" 100mm 100OZ

SPL: 126dB

DSP: 48KHz Sampling Frequency 24 Bit

Amp Type: Class D

Amp Power: 800RMS

Peak Power: 1600W

Dimension(WxHxD): 720x610x685mm

Weight: 40kg

SPEAKERS



M50
BI-AMPED TWO WAY
ACTIVE STUDIO MONITOR
(PAIR)

Type: Biamp Two Way Active Speaker
Power handling: 50W
Frequency Response-10dB: 55Hz-22kHz
Woofers: 5.25" Coating-Paper Cone
Tweeter: 1" Silk Dome
SPL: 108dB
Input-XLR Balanced / RCA Unbalanced
Variable High & Low Frequency Adjustments



M60
BI-AMPED TWO WAY
ACTIVE STUDIO MONITOR
(PAIR)

Type: Biamp Two Way Active Speaker
Power handling: 60W
Frequency Response-10dB: 45Hz-22kHz
Woofers: 6.5" Coating-Paper Cone
Tweeter: 1" Silk Dome
SPL: 111dB
Input-XLR Balanced / RCA Unbalanced
Variable High & Low Frequency Adjustments



Inputs: Bal XLR/TRS 6.35/Aux/Bluetooth
Outputs: Balanced XLR / TWS
Power Output: 150W (LF) + 50W (HF) RMS
Bluetooth Version: 5.0
Power Input: 100V/240V~50/60Hz switchable
Single Processing: DSP
DSP Preset: 4
Frequency Range: 60-20kHz
Max Output SPL: 123dB (at max AMP output)
Impedance: LF 4Ω/HF 8Ω
Driver: 1" Compression Driver
Woofers: 10" Driver
Pole Mount: 35mm Stand Pole

PRO-X 10
200W
Powered Loudspeaker



PRO-X 12
300W
Powered Loudspeaker

Inputs: Bal XLR/TRS 6.35/Aux/Bluetooth
Outputs: Balanced XLR / TWS
Power Output: 250W (LF) + 50W (HF) RMS
Bluetooth Version: 5.0
Power Input: 100V/240V~50/60Hz switchable
Single Processing: DSP
DSP Preset: 4
Frequency Range: 55-20kHz
Max Output SPL: 125dB (at max AMP output)
Impedance: LF 4Ω/HF 8Ω
Driver: 1.35" Compression Driver
Woofers: 12" Driver
Pole Mount: 35mm Stand Pole



PRO-X 15
300W
Powered Loudspeaker



Inputs: Bal XLR/TRS 6.35/Aux/Bluetooth
Outputs: Balanced XLR / TWS
Power Output: 250W (LF) + 50W (HF) RMS
Bluetooth Version: 5.0
Power Input: 100V/240V~50/60Hz switchable
Single Processing: DSP
DSP Preset: 4

Frequency Range: 45-20kHz
Max Output SPL: 126dB (at max AMP output)
Impedance: LF 4Ω/HF 8Ω
Driver: 1.35" Compression Driver
Woofers: 15" Driver
Pole Mount: 35mm Stand Pole

SPEAKERS



PRO-X 115S

1000W

Active Subwoofer

Power Output: 550W
Power (Peak): 1000W
Amplifier: Class-D
Max. SPL: 126dB
Impedance: 8Ohm
Frequency Range: 35-160Hz
Woofers: 15"/3" Voice Coil
DSP: Yes

Connection: 2X XLR /Jack (6,35mm)-Combination jack
Output: 2X XLR
Power Supply: 220-240V, 50/60Hz
Mains Connection: Power Outlet
Case: 2 lateral recessed handles, solid rubber feet



PRO-X 118S

1000W

Active Subwoofer

Inputs: 2XLR/TRS Line input
Outputs: 2 XLR line output
Power Output: 500W/RMS@ 8Ohms/1500W Peak
Volume: Main Volume Control
Power Input: 100V/240V~50/60Hz switchable
Class D+ switching power design
Phase switchable(0/180Degree)
Led power/signal/clip indicator

Crossover design for satellite (90Hz or 120Hz)
Type: Active vented Subwoofer
Frequency Response: 35-150Hz
Max Output SPL: 125dB
Impedance: 8Ohm
Woofers: 18" subwoofer, 3" VC 850Z (MA 18SW)
Pole: 35mm stand pole



PRO-X SM12

350W

Stage Monitor



PRO-X SM15

350W

Stage Monitor




Inputs: Bal XLR/TRS 6.35mm
Outputs: Balanced XLR
Power Output: 350W RMS
Power Input: 110V/220V~60/50 Hz switchable
Features: BI-AMP coaxial speaker
LF:Class-D HF:Class AB
Signal Processing: DSP
DSP Preset: 4

Frequency Range: 65Hz-20KHz
Max Output SPL: 123dB
Sensitivity: 95dB
Woofers: 12"; 2.5" VC;430Z
Driver: 1.35" Ferrite CD
Cabinet: PLY painted cabinet
Pole Mount: 35mm stand pole

Inputs: Bal XLR/TRS 6.35mm
Outputs: Balanced XLR
Power Output: 350W RMS
Power Input: 110V/220V~60/50 Hz switchable
Features: BI-AMP coaxial speaker
LF:Class-D HF:Class AB
Signal Processing: DSP
DSP Preset: 4

Frequency Range: 55Hz-20KHz
Max Output SPL: 124dB
Sensitivity: 96dB
Woofers: 15"; 2.5" VC;430Z
Driver: 1.35" Ferrite CD
Cabinet: PLY painted cabinet
Pole Mount: 35mm stand pole


SPEAKERS



VIBE PRO+ 12
2000W
Active Speaker

Woofer: 1*12" Woofer
Tweeter: 1"1.35" compress driver
Power (w): 1000W + 1000W(RMS)
Peak SPL(dB): 129
Frequency Range: 50Hz-20kHz
Link: Wire & TWS

Input: Combo*2, Bluetooth*1
Output: XLR*1
Pole: 35mm stand screen
LCD: 2.4in color screen



VIBE PRO+ 15
2000W
Active Speaker

Woofer: 1*15" Woofer
Tweeter: 1"1.35" compress driver
Power (w): 1000W + 1000W(RMS)
Peak SPL(dB): 130
Frequency Range: 40Hz-20kHz
Link: Wire & TWS

Input: Combo*2, Bluetooth*1
Output: XLR*1
Pole: 35mm stand screen
LCD: 2.4in color screen



VIBE PRO+ 118S

4000W
Active Subwoofer

Woofer: 1*18" Woofer
Peak Power (w): 4000w
Peak SPL(dB): 135
Frequency Range: 40Hz-120kHz
Link: Wire
Input: Combo*2
Output: XLR*2
Pole: 35mm stand screen
LCD: 2.4in color screen

MICROPHONE STANDS



HMS65

Microphone Stand

- Strong, tip-resistant tripod base.
- Scratch-resistant powder coat finish.
- Nylon leg housing for dependable base support.
- Non-slip rubber feet.
- Boom Length: 800mm.
- Height: 1000mm – 1800mm.
- Threading: 5/8".



HMS65T

Microphone Stand

- Strong, tip-resistant tripod base.
- Scratch-resistant powder coat finish.
- Nylon leg housing for dependable base support.
- Non-slip rubber feet.
- Boom Length: 800mm.
- Height: 1000mm – 1800mm.
- Threading: 5/8".



HMS65S

Microphone Stand

- Strong, tip-resistant tripod base.
- Scratch-resistant powder coat finish.
- Nylon leg housing for dependable base support.
- Non-slip rubber feet.
- Boom Length: 800mm.
- Height: 1000mm – 1800mm.
- Threading: 5/8".



HMS30TB

Microphone Stand

- Strong, tip-resistant tripod base.
- Scratch-resistant powder coat finish.
- Nylon leg housing for dependable base support.
- Non-slip rubber feet.
- Boom Length: 800mm.
- Height: 1000mm – 1800mm.
- Threading: 5/8".



MS50

Short Microphone Stand

- Strong, tip-resistant tripod base.
- Scratch-resistant powder coat finish.
- Nylon leg housing for dependable base support.
- Non-slip rubber feet.
- Boom Length: 800mm.
- Height: 1000mm – 1800mm.
- Threading: 5/8".



MS100

Microphone Stand

- Strong, tip-resistant tripod base.
- Scratch-resistant powder coat finish.
- Nylon leg housing for dependable base support.
- Non-slip rubber feet.
- Boom Length: 20" - 35.8" / 51 cm-91cm
- Height: 39" - 62" / 100cm - 160 cm.
- Threading: 5/8" -27".

MICROPHONE STANDS



TS100 *Microphone Stand*

- Strong, tip-resistant tripod base.
- Scratch-resistant powder coat finish.
- Nylon leg housing for dependable base support.
- Non-slip rubber feet.
- Boom Length: 20" - 35.8" / 51 cm-91cm
- Height: 39" - 62" / 100cm - 160 cm.
- Threading: 5/8" -27".



HMS30FB

Heavy Base Microphone Stand

- Strong, tip-resistant tripod base.
- Scratch-resistant powder coat finish.
- Nylon leg housing for dependable base support.
- Non-slip rubber feet.
- Boom Length: 800mm.
- Height: 1000mm – 1800mm.
- Threading: 5/8".

SPEAKER STANDS



HAS01 *Microphone Stand*

- The adjustable Black Scissor Arm Stand is made of high quality steel frame, plastic Mic Clip (INCLUDED), sturdy and durable.
- Scissor Arm Stand : The adjustable arms can be fold up and easy for you to carry around and allow you to adjust the suitable angle and height to show your perfect voice.
- Universal mounting clamp attaches to tables, desks, shelves, counters, etc. Suitable for any stores, families, stages, studios, broadcasting and TV stations, etc. with an adjustable positioning screw, can easily clip to any desktop up to 1.7"/4.5cm thick.



HMPS001

Studio Monitor Stand

- Height-adjustable stand for studio monitors.
- Locking pin ensures stable and accurate height positions.
- Leveling floor spikes and rubber feet included.
- Low-profile base can be easily positioned into tight spaces.
- Platform Dimensions: 9" x 9" (229mm x 229mm).
- Base Dimensions: 17.25" x 17.25" x 17.25" (438mm x 438mm x 438mm).
- Weight Capacity: 25 Kgs per Stand.



HSBP001 *Sub Woofer Pole*

- Heavy-duty construction.
- Height adjustable.
- Friction locking knob with security pin.



HSBPM20 *Sub Woofer Pole*

- Heavy-duty construction.
- Height adjustable.
- Friction locking knob with security pin.

SPEAKER STANDS



HSP001 *Speaker Tripod Stand*

- Heavy-duty construction.
- Height adjustable.
- Friction locking knob with security pin.

WALL MOUNT SPEAKER STANDS



HW001

Wall Mount Speaker Stand

- Heavy-duty nut and bolt support 40 Kgs and swivel 90° left and 90 right.
- 1 3/8" speaker pole mounts a wide range of speakers.
- Adjustable tilt angle enables speakers to point either straight ahead or up to 45° down.
- Adjustable tilt angle at base up to 45° down.

WALL MOUNT SPEAKER STANDS



HW002

Wall Mount Speaker Stand

- Application: Small to medium speaker cabinet wall mount
- Weight Capacity: 40 kg
- Tilt Angle Adjustment: 45 Degree
- Sideways Adjustment: 90 Degree
- Construction: Steel
- Color: Black

KEYBOARD STANDS



PROMAX

Double Keyboards Stand

- Foldable and compact but solid structure
- Supporting arms of adjustable height
- 6063T-6 Aluminum for the mast
- A360 Aluminum for connection parts, Plastic wire clip
- Load capacity: Upper layer: 20kg, Lower layer: 40kg
- Suitable for various keyboards



HX200

Double Teir Keyboard Stand

- Adjustable height, suitable for any venue. Piano stand features rubber hands, feet, and stability straps all designed secure your keyboard or digital piano in place.



HX001

Assembled Single-braced X-style Stand

- Assembled single-braced X-style stand
- Strong, sturdy steel design
- Five height positions
- Folds flat for simple storage and transport
- Rubber end caps keeps instrument scratch-free
- Height: 641mm – 978mm
- Leg Depth: 476mm
- Arm Depth: 337mm
- Steel Tubing: 25mm
- Load Capacity: 45

KEYBOARD STANDS

HX002

Double-braced for heavier keyboards



- Double-braced for heavier keyboards
- Five height positions
- Easy-to-adjust pull-style knob locks stand in place
- Constructed from strong steel tubing
- Height: 648mm – 965mm
- Leg Depth: 489mm
- Arm Depth: 400mm
- Steel Tubing: 25mm
- Load Capacity: 57 kg

HX003

Assembled single-braced X-style stand




- Assembled single-braced X-style stand
- Strong, sturdy steel design
- Five height positions adjusted by knob
- Folds flat for simple storage and transport
- Rubber end caps keeps instrument scratch-free
- Height: 641mm – 978mm
- Leg Depth: 476mm
- Arm Depth: 337mm
- Steel Tubing: 25mm
- Load Capacity: 45

KEYBOARD STANDS

HX004

Double-braced for heavier keyboards



- Double-braced for heavier keyboards
- Five height positions adjusted by knob
- Constructed from strong steel tubing
- Height: 648mm – 965mm
- Leg Depth: 489mm
- Arm Depth: 400mm
- Steel Tubing: 25mm
- Load Capacity: 57 kg

GUITAR STAND

HGS001

A Style Guitar Stand for Electric, Bass, Acoustic Guitar



- Application: A-Style Guitar Stand
- Width : 190-350 mm
- Height Adjustment: 420 mm
- Construction: Steel

GUITAR STAND

HGS002

Adjustable Guitar Stand For Electric, Bass, Acoustic Guitar



- Application: Guitar Stand
- Height Adjustment: 660-780 mm
- Construction: Steel

MUSIC SHEET STAND

HMU001

Heavy Duty Music Stand



- Professional collapsible music stand made of durable and heavy duty metal.
- No worry about the loading capacity of this Music Stand with sturdy metal tripod legs, which have non-slip rubber caps on the bottom that secure at any height.

SNAKE CABLE

20 Channel Ready-Made Snake Cable With Drum



MODEL	SIZE
HSD1604LU30	30M
HSD1604LU50	50M

- Snake Cable on a Reel.
- All XLR Connections.
- 16 XLR Female Connectors.
- 4 XLR Male Connectors.
- Well labeled on both ends.
- Fantail is color coded and numerically labeled.
- 100% individually shielded pairs.
- Heavy Duty Steel Reel.
- High quality XLR connectors on both ends.
- One Year Warranty.

24 Channel Ready-Made Snake Cable With Drum



MODEL	SIZE
HSD1608LU30	30M
HSD1608LU50	50M

32 Channel Ready-Made Snake Cable With Drum



MODEL	SIZE
HSD2408LU30	30M
HSD2408LU50	50M

- Snake cable.
- All XLR connections.
- 24 XLR Female connectors.
- 8 XLR Male connectors.
- Well labeled on both ends.
- Fantail is color coded and numerically labeled.
- 100% individually shielded pairs.
- Heavy duty steel reel.
- High quality XLR connectors on both ends.
- One year warranty.

40 Channel Ready-Made Snake Cable With Drum



MODEL	SIZE
HSD3208LU30	30M
HSD3208LU50	50M

20 Channel Ready-made Drum Snake Cable With Neutrik Connectors



MODEL	SIZE
HNSD1604LU30	30M
HNSD1604LU50	50M

- 16 XLR Female Connectors.
- 4 XLR Male Connectors.
- Neutrik XLR Male to Female connector
- Fantail is color coded and numerically labeled.
- Heavy Duty Steel reel.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

24 Channel Ready-made Drum Snake Cable With Neutrik Connectors



MODEL	SIZE
HNSD1608LU30	30M

32 Channel Ready-made Drum Snake Cable With Neutrik Connectors



MODEL	SIZE
HNSD2408LU30	30M
HNSD2408LU50	50M

- 24 XLR Female Connectors.
- 8 XLR Male Connectors.
- Neutrik XLR Male to Female connector
- Fantail is color coded and numerically labeled.
- Heavy Duty Steel reel.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

40 Channel Ready-made Drum Snake Cable With Neutrik Connectors



MODEL	SIZE
HNSD3208LU30	30M
HNSD3208LU50	50M

SNAKE CABLE

12 Channel Ready-made Snake Cable With Neutrik Connectors



MODEL	SIZE
HNSS804LU10	10M
HNSS804LU15	15M
HNSS804LU20	20M
HNSS804LU30	30M

- 8 XLR Female Connectors.
- 4 XLR Male Connectors.
- Neutrik XLR Male to Female connector
- Fantail and Stage Box are both clearly Numerically Labeled.
- Fantail is color coded as well.
- Heavy Duty Steel Stage Box with Handle.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

16 Channel Ready-made Snake Cable With Neutrik Connectors



MODEL	SIZE
HNSS1204LU15	15M
HNSS1204LU30	30M

- 12 XLR Female Connectors.
- 4 XLR Male Connectors.
- Neutrik XLR Male to Female connector
- Fantail and Stage Box are both clearly Numerically Labeled.
- Fantail is color coded as well.
- Heavy Duty Steel Stage Box with Handle.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

32 Channel Ready-made Snake Cable With Neutrik Connectors



MODEL	SIZE
HNSS2408LU30	30M

- 24 XLR Female Connectors.
- 8 XLR Male Connectors.
- Neutrik XLR Male to Female connector
- Fantail and Stage Box are both clearly Numerically Labeled.
- Fantail is color coded as well.
- Heavy Duty Steel Stage Box with Handle.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

40 Channel Ready-made Snake Cable With Neutrik Connectors



MODEL	SIZE
HNSS3208LU30	30M

- 32 XLR Female Connectors.
- 8 XLR Male Connectors.
- Neutrik XLR Male to Female connector
- Fantail and Stage Box are both clearly Numerically Labeled.
- Fantail is color coded as well.
- Heavy Duty Steel Stage Box with Handle.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

12 Channel Ready-Made Snake Cable



MODEL	SIZE
HSS804LU10	10M
HSS804LU15	15M
HSS804LU20	20M

- 8 XLR Female Connectors.
- 4 XLR Male Connectors.
- Heavy Duty Steel Stage Box with Handle.
- Fantail and Stage Box are both clearly Numerically Labeled.
- Fantail is color coded as well.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

16 Channel Ready-Made Snake Cable



MODEL	SIZE
HSS1204LU15	15M
HSS1204LU30	30M

- 12 XLR Female Connectors.
- 4 XLR Male Connectors.
- Heavy Duty Steel Stage Box with Handle.
- Fantail and Stage Box are both clearly Numerically Labeled.
- Fantail is color coded as well.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

20 Channel Ready-Made Snake Cable



MODEL	SIZE
HSS1604LU15	15M
HSS1604LU30	30M

- 16 XLR Male Connectors.
- 4 XLR Female Connectors.
- Heavy Duty Steel Stage Box with Handle.
- Fantail and Stage Box are both clearly Numerically Labeled.
- Fantail is color coded as well.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

24 Channel Ready-Made Snake Cable



MODEL	SIZE
HSS1608LU30	30M

- 16 XLR Female Connectors.
- 8 XLR Male Connectors.
- Heavy Duty Steel Stage Box with Handle.
- Fantail and Stage Box are both clearly Numerically Labeled.
- Fantail is color coded as well.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

SNAKE CABLE



32 Channel Ready-Made Snake Cable

MODEL	SIZE
HSS2408LU30	30M
HSS2408LU50	50M



40 Channel Ready-Made Snake Cable

MODEL	SIZE
HSS3208LU30	30M
HSS3208LU50	50M

- 24 XLR Female Connectors.
- 8 XLR Male Connectors.
- Heavy Duty Steel Stage Box with Handle.
- Fantail and Stage Box are both clearly Numerically Labeled.

- Fantail is color coded as well.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

- 32 XLR Female Connectors.
- 8 XLR Male Connectors.
- Heavy Duty Steel Stage Box with Handle.
- Fantail and Stage Box are both clearly Numerically Labeled.

- Fantail is color coded as well.
- 100% Individually Shielded Pairs.
- High Quality XLR connectors at both ends.
- One Year Warranty.

Stage Box with Cable 16 Channel



MODEL	SIZE
HSS88LU06	6M

- 8*XLR (female) + 8*1/4" TRS (Female) on the box.
- 8*XLR (Male) + 8*1/4" TRS (Male) on other end.

- Oxygen free copper cable.
- Numbering on cable for easy identification.
- One year warranty.

Stage Box with Cable 8 Channel



MODEL	SIZE
HSS44LU03	3M
HSS44LU05	5M

- 4*XLR (female) + 4*1/4" TRS (Female) on the box.
- 4*XLR (Male) + 4*1/4" TRS (Male) on other end.

- Oxygen free copper cable.
- Numbering on cable for easy identification.
- One year warranty.

Stage Box with Cable 12 Channel



MODEL	SIZE
HSS84LU03	3M
HSS84LU05	5M

- 8*XLR (female) + 4*1/4" TRS (Female) on the box.
- 8*XLR (Male) + 4*1/4" TRS (Male) on other end.

- Numbering on cable for easy identification.
- Oxygen free copper cable.
- One year warranty.



HSX4LU03 4 Channel Short Snake Cable

MODEL	SIZE
HSX4LU03	3M
HSX4LU05	5M

- 3 Meters / 9.84 Foot.
- 4 * XLR Male at one end.
- 4 * XLR Female at other end.
- Oxygen Free Cooper.

- One Year Warranty.
- Ideal for Patch Bays / Multi-Track Recorders / Mixers / Audio Interfaces.



HST4LU03 4 Channel Short Snake Cable

MODEL	SIZE
HST4LU03	3M
HST4LU05	5M

- 3 Meters / 9.84 Foot.
- 4 * TRS Male at one end.
- 4 * TRS Male at other end.
- Oxygen Free Cooper.

- One Year Warranty.
- Ideal for Patch Bays / Multi-Track Recorders / Mixers / Audio Interfaces.



HSX8LU05 8 Channel Short Snake Cable

MODEL	SIZE
HSX8LU03	3M
HSX8LU05	5M

- 5 Meters / 16.40 Foot.
- 8 * XLR Male at one end.
- 8 * XLR Female at other end.
- Oxygen Free Cooper.

- One Year Warranty.
- Ideal for Patch Bays / Multi-Track Recorders / Mixers / Audio Interfaces.

SNAKE CABLE/CABLE ROLL



HXT8LU03
8 CHANNEL SHORT
SNAKE CABLE

- 3 Meters / 9.84 Foot.
- One Year Warranty.
- 8 * XLR Male at one end.
- Ideal for Patch Bays / Multi-Track
- 8 * TRS Male at other end.
- Recorders / Mixers / Audio
- Oxygen Free Cooper.
- Interfaces.

4 Channel Multicore Snake Cable



- 4*2*0.14mm²(AWG26).
- High quality oxygen free copper cable.
- One year warranty.

Model No.	Length
HMSC04	100 Mtr.

8 Channel Multicore Snake Cable



- 8*2*0.14mm²(AWG26).
- High quality oxygen free copper cable.
- One year warranty.

Model No.	Length
HMSC08	100 Mtr.

12 Channel Multicore Snake Cable



- 12*2*0.14mm²(AWG26).
- High quality oxygen free copper cable.
- One year warranty.

Model No.	Length
HMSC12	100 Mtr.

16 Channel Multicore Snake Cable



- 16*2*0.14mm²(AWG26).
- High quality oxygen free copper cable.
- One year warranty.

Model No.	Length
HMSC16	33 Mtr.
HMSC16	50 Mtr.
HMSC16	100 Mtr.

20 Channel Multicore Snake Cable



- 20*2*0.14mm²(AWG26).
- High quality oxygen free copper cable.
- One year warranty.

Model No.	Length
HMSC20	33 Mtr.
HMSC20	50 Mtr.
HMSC20	100 Mtr.

24 Channel Multicore Snake Cable



- 24*2*0.14mm²(AWG26).
- High quality oxygen free copper cable.
- One year warranty.

Model No.	Length
HMSC24	33 Mtr.
HMSC24	50 Mtr.
HMSC24	100 Mtr.

32 Channel Multicore Snake Cable



- 32*2*0.14mm²(AWG26).
- High quality oxygen free copper cable.
- One year warranty.

Model No.	Length
HMSC32	33 Mtr.
HMSC32	50 Mtr.
HMSC32	100 Mtr.

40 Channel Multicore Snake Cable



- 40*2*0.14mm²(AWG26).
- High quality oxygen free copper cable.
- One year warranty.

Model No.	Length
HMSC40	33 Mtr.
HMSC40	50 Mtr.
HMSC40	100 Mtr.



HSP210LU100

2*1.0 MM² (AWG17) /
OFC SPEAKER CABLE /
BLACK COLOR /100 METERS /
PLASTIC SPOOL

CABLE ROLL



HSP213LU100

2*1.3 MM2 (AWG16) /
OFC SPEAKER CABLE /
BLACK COLOR /100 METERS /
PLASTIC SPOOL



HSP215LU100

2*1.5 MM2 (AWG15) /
OFC SPEAKER CABLE /
BLACK COLOR /100 METERS /
PLASTIC SPOOL



HSP220LU100

2*2.0 MM2 (AWG14) /
OFC SPEAKER CABLE /
BLACK COLOR /100 METERS /
PLASTIC SPOOL



HSP225LU100

2*2.5 MM2 (AWG13) /
OFC SPEAKER CABLE /
BLACK COLOR /100 METERS /
WOODEN SPOOL



HSP415LU100

4*1.5 MM2 (AWG15) /
OFC SPEAKER CABLE /
BLACK COLOR /100 METERS /
WOODEN SPOOL



HSP425LU100

4*2.5 MM2 (AWG13) /
OFC SPEAKER CABLE /
BLACK COLOR /100 METERS /
WOODEN SPOOL



HGP2075LU100

2*0.75 MM2 (AWG18) /
OFC SPEAKER CABLE /
GREY /100 METERS /
PLASTIC SPOOL



HGP210LU100

2*1.0 MM2 (AWG17) /
OFC SPEAKER CABLE /
GREY /100 METERS /
PLASTIC SPOOL



HGP213LU100

2*1.3 MM2 (AWG16) /
OFC SPEAKER CABLE /
GREY /100 METERS /
PLASTIC SPOOL



HGP215LU100

2*1.5 MM2 (AWG15) /
OFC SPEAKER CABLE /
GREY /100 METERS /
PLASTIC SPOOL



HGP225LU100

2*2.5 MM2 (AWG13) /
OFC SPEAKER CABLE /
GREY /100 METERS /
WOODEN SPOOL



HTWP2075 LU100

2*0.75 MM2 (AWG18) /
OFC SPEAKER CABLE /
TWIN CABLE

CABLE ROLL



HTWP210LU100
2*1.0 MM2 (AWG17) /
OFC SPEAKER CABLE /
TWIN CABLE



HTWP213LU100
2*1.3 MM2 (AWG16) /
OFC SPEAKER CABLE /
TWIN CABLE



HTWP215LU100
2*1.5 MM2 (AWG15) /
OFC SPEAKER CABLE /
TWIN CABLE



HMC012-BK
Microphone Roll Cable 100 Meters

- 24 AWG.
- Oxygen free copper .
- Shield - 64X0.12.
- Inner conductor (20X.12) X2.
- OD 60mm.



HMC012-BL
Microphone Roll Cable 100 Meters

- 24 AWG.
- Oxygen free copper .
- Shield - 64X0.12.
- Inner conductor (20X.12) X2.
- OD 60mm.



HMC012-PRL
Microphone Roll Cable 100 Meters

- 24 AWG.
- Oxygen free copper .
- Shield - 64X0.12.
- Inner conductor (20X.12) X2.
- OD 60mm.



HMC012-GR
Microphone Roll Cable 100 Meters

- 24 AWG.
- Oxygen free copper .
- Shield - 64X0.12.
- Inner conductor (20X.12) X2.
- OD 60mm.



HMC012-OR
Microphone Roll Cable 100 Meters

- 24 AWG.
- Oxygen free copper .
- Shield - 64X0.12.
- Inner conductor (20X.12) X2.
- OD 60mm.



HMC012-RD
Microphone Roll Cable 100 Meters

- 24 AWG.
- Oxygen free copper .
- Shield - 64X0.12.
- Inner conductor (20X.12) X2.
- OD 60mm.



HDMX04LU100
Gold Series DMX or AESEBU Cable



HDMX24LU100
Premium Series DMX or AESEBU Cable



PTMC34LU100
Platinum Series Microphone Cable



PSMC22LU100
Premium Series Microphone Cable

CABLE/CONNECTOR



HC2PLU01.8
TYPE C TO
2*6.35MM TS MALE



HC2RLU01.8
TYPE C TO
2*RCA MALE

CABLE



HC2XMLU01.8

TYPE C TO 2* XLR MALE



HCJFLU00.15

TYPE C TO 3.5MM TRS FEMALE



HCJLU01.8

TYPE C TO 3.5MM TRS MALE



HCPLU01.8

TYPE C TO 6.35MM TS MALE



HCTLU01.8

TYPE C TO 6.35MM TRS MALE



HGTRLU03

1/4" TS MALE TO
1/4" TS MALE

Model No.	Length
HGTRLU03	3 M
HGTRLU05	5 M



HMSPLU01

1/4" TRS MALE TO 1/4" TRS MALE

Model No.	Length
HMSPLU01	1 M
HMSPLU01	3 M
HMSPLU01	5 M



HXRLU03

XLR MALE TO FEMALE

Model No.	Length
HXRLU03	3 M
HXRLU05	5 M



HXFPLU01

XLR MALE TO FEMALE

Model No.	Length
HXFPLU01	1 M
HXFPLU03	3 M
HXFPLU05	5 M
HXFPLU10	10 M



HXSPLU02

XLR MALE TO 1/4" TRS MALE

Model No.	Length
HXSPLU02	2 M
HXSPLU03	3 M
HXSPLU05	5 M



NEUTRIK CABLE

NXFP003

XLR MALE TO FEMALE

Model No.	Length
NXFP003	3 M
NXFP006	6 M
NXFP010	10 M
NXFP016	16 M
NXFP033	33 M
NXFP050	50 M



PATCH CABLE

HSBRJ45LU01

CAT6 PATCH CABLE

Model No.	Length
HSBRJ45LU01	1 M
HSBRJ45LU02	2 M
HSBRJ45LU03	3 M
HSBRJ45LU05	5 M
HSBRJ45LU10	10 M
HSBRJ45LU50	50 M
HSBRJ45LU75	75 M

CABLE



HRJ5ELU02
CAT5E PATCH CABLE

Model No.	Length
HRJ5ELU02	2 M
HRJ5ELU03	3 M
HRJ5ELU05	5 M
HRJ5ELU10	10 M



HRJ45LU01
CAT6 PATCH CABLE

Model No.	Length
HRJ45LU01	1 M
HRJ45LU02	2 M
HRJ45LU03	3 M
HRJ45LU05	5 M



HRJ45DLU50
CAT6 PATCH CABLE 50 M



HSBRJ45DLU75
CAT6 PATCH CABLE 75 M



Hi520/50 CAT5E
CAT5E PATCH CABLE 20/50 M



Hi520/50 CAT6
CAT6 PATCH CABLE 20/50 M



STXFLU
*3.5 MM TRS MALE
TO XLR FEMALE*

Model No.	Length
STXFLU 03	3 M
STXFLU 05	5 M



STMLU
*3.5MM TRS MALE
TO 3.5MM TRS MALE*

Model No.	Length
STMLU 0.5	1.5M
STMLU 03	3 M



SFFLU00.15
*Y CABLE 6.3MM TRS MALE
TO DUAL 6.3MM TRS FEMALE
6 INCH*



TMRLU03
*Y CABLE 3.5MM TRS MALE
TO DUAL RCA MALE*



SFPG010
XLR FEMALE TO TS MALE 3M

Model No.	Length
SFPG 010	10 FEET
SFPG 016	16 FEET



TMPLU01.5
*Y CABLE 3.5MM TRS MALE
TO DUAL TS MALE*

Model No.	Length
TMPLU 01.5	1.5 M
TMPLU 03	3 M

CABLE



SMPG
TS MALE TO TS MALE
16 FEET

Model No.	Length
SMPG 010	10 FEET
SMPG 016	16 FEET



SFSLU03
6.3 MM TRS MALE
TO 6.3MM TRS FEMALE 3M



STXM010
3.5MM TRS MALE TO
XLR MALE 10 FEET



STXF
3.5MM TRS MALE TO
XLR FEMALE

Model No.	Length
STXF 010	10 FEET
STXF 020	20 FEET
STXF 033	33 FEET



SMPLU03
Y CABLE TRS MALE TO
DUAL TS MALE 3M



TMXLU03
Y CABLE 3.5 MM STEREO
MALE TO DUAL XLR MALE-3 METER



SMSG
1/4" TRS MALE TO 1/4" TRS MALE

Model No.	Length
SMSG 005	05 FEET
SMSG 010	10 FEET
SMSG 016	16 FEET

SXFG
XLR Male to
XLR Female

Model No.	Length	Model No.	Length
SXFG 003	3 FEET	SXFG 016	16 FEET
SXFG 005	5 FEET	SXFG 033	33 FEET
SXFG 010	10 FEET	SXFG 050	50 FEET
		SXFG 066	66 FEET



TMSLU03
3.5MM TRS MALE TO
6.3MM TRS MALE



SXSG
XLR MALE TO
1/4" TRS MALE

Model No.	Length
SXSG 005	5 FEET
SXSG 010	10 FEET
SXSG 016	16 FEET



SXFG010 BLU

XLR Male to XLR Female 10 feet



SXFG010 PRL

XLR Male to XLR Female 10 feet



SXFG010 RED

XLR Male to XLR Female 10 feet



SXFG010 GRN

XLR Male to XLR Female 10 feet



SXFG010 ORG

XLR Male to XLR Female 10 feet



TC10

3.5MM TRS EXTENSION
CABLE



STTF2X006

3.5MM TRS Male to Dual
3.5MM Female 6 Inch



STTM2X006

3.5MM TRS Female to
2X3.5MM male 6 Inch



TC1

TRRS EXTENSION CABLE
6M/20 FEET



TC3

3.5MM TRS TO TRRS PATCH
CABLE 10 CM

CABLE/CONNECTOR

			
TC4 3.5MM TRS FEMALE TO TRRS MALE 10 CM	NMSG010 3M	NXSP010 3M	NXFP010 3M
			
HSTM-S TRS MALE SILVER	HSTM-SG TRS MALE SILVER (GOLD TIP)	HTM-S TS MALE SILVER	HTM-SG TS MALE SILVER (GOLD TIP)
			
HXF-S XLR FEMALE SILVER	HXM-S XLR MALE SILVER	HC2F XLR / TRS COMBO SOCKET (FEMALE)	HMJ-BG 3.5MM STEREO
			
HMJ-S 3.5MM STEREO	HPC1 POWERCON	HPC2 POWERCON	HRM-BG RCA MALE
			
HRM-SG RCA MALE	HSP01 SPEAKON	HSP80 SPEAKON	HSP81 SPEAKON
			
HSTM81-BG TRS 6.35MM STEREO GOLD	HSTM81-S TRS MALE 6.35MM STEREO GOLD	HT2F TRS FEMALE SOCKET	HTS81-BG TS 6.35MM MONO GOLD

CABLE/CONNECTOR



HTS81R-BG
TS MONO RIGHT ANGLE



HTS81R-S
TS MONO RIGHT ANGLE



HTS81-S
TS 6.35MM MONO



HX2F
XLR FEMALE SOCKET



HX2M
XLR MALE SOCKET



HX81F-S
XLR MALE



HX81M-S
XLR FEMALE

DB CABLE



HDTM803
DB25 TO XLR FEMALE



HDTF803
DB25 TO XLR MALE



HDTP803
DB25 TO TS MALE

EMPTY DRUM



ED320P
EMPTY PLASTIC DRUM FOR
SNAKE CABLE



ED380M
EMPTY METAL DRUM FOR
SNAKE CABLE



ED470M
EMPTY METAL DRUM FOR
SNAKE CABLE



ED530M
EMPTY METAL DRUM FOR
SNAKE CABLE



ED380P
EMPTY PLASTIC DRUM FOR
SNAKE CABLE

STAGE BOX WITH COMBO JACK



SB804

- 8 XLR female input.
- 4 XLR male output.
- Heavy duty steel.
- Cover included.
- One year warranty.



SB1604

- 16 XLR female input.
- 4 XLR male output.
- Heavy duty steel.
- One year warranty.



SB3208

- 32 XLR female input.
- 8 XLR male output.
- Heavy duty steel.
- One year warranty.



SB12IN

- 12 XLR female input.
- Heavy duty steel.
- One year warranty.



SB1608

- 16 XLR female input.
- 8 XLR male output.
- Heavy duty steel.
- One year warranty.



SBC8IN

- 4 XLR female input.
- 4 XLR combo jack input.
- Heavy duty steel.
- Cover included.
- One year warranty.



SBC804

- 4 XLR female input.
- 4 XLR combo jack input.
- 4 XLR male output.
- Heavy duty steel.
- Cover included.
- One year warranty.



SBC12IN

- 8 XLR female input.
- 4 XLR combo jack input.
- Heavy duty steel.
- Cover included.
- One year warranty.



SBC1204

- 8 XLR female input.
- 4 XLR combo jack input.
- 4 XLR male output.
- Heavy duty steel.
- Cover included.
- One year warranty.



SBC1604

- 12 XLR female input.
- 4 XLR combo jack input.
- 4 XLR male output.
- Heavy duty steel.
- Cover included.
- One year warranty.



SBC1608

- 12 XLR female input.
- 4 XLR combo jack input.
- 8 XLR male output.
- Heavy duty steel.
- Cover included.
- One year warranty.



SBC2408

- 16 XLR female input.
- 8 XLR combo jack input.
- 8 XLR male output.
- Heavy duty steel.
- One year warranty.

STAGE BOX WITH COMBO JACK



SB8IN

- 8 XLR female input.
- Heavy duty steel.
- One year warranty.



SB1212

- 12 XLR female input.
- 12 XLR male output.
- Heavy duty steel.
- One year warranty.



SB2408

- 24 XLR female input.
- 8 XLR male output.
- Heavy duty steel.
- One year warranty.

POWER SEQUENCER



HZ-8N

AC POWER SEQUENCER

- 8-way output.
- Main power supply voltage monitor.
- Sequential control circuit preset interval 1 second.
- 2U standard model.
- Output controlled by MCU, sequential on or anti-sequential switch off.
- Network function, remote control.



HZ-12N

AC POWER SEQUENCER

- 12-way output.
- Main power supply voltage monitor.
- Sequential control circuit preset interval 1 second.
- 3U standard model.
- Output controlled by MCU, sequential on or anti-sequential switch off.
- Network function, remote control.



PS-8

Single Phase Power Sequencer

- This sequencer is a compact size, powerful intelligent timing device. It combines the function of many conventional products in.
- LCD screen displaying the ID, year, month, day, time and IP address.
- Voltage indicate: input and output voltage indicator
- Current indicate: input and output current indicator
- Power switch: power switch with earth leakage protection.



K108

Intelligent Power Supply Sequencer

- This sequencer is a compact volume, simple operation of 8 intelligent power supply sequencer, with air switch mainly used in a bar or hall performance with high power requirements.
- 8-Channel output, 16A universal socket
- Support channel 1 second interval timing switch control.
- Supports cascading control of 2 devices.
- Support external switching signals to trigger sequencer startup and shutdown.



PS108A

Intelligent Power Supply Sequencer


















- This sequencer is a compact size, powerful intelligent timing device. It combines the function of many conventional products in.
- 8-Channel output, 16A universal socket
- Support lock function for panel, which avoids misoperation.
- Supports cascading control of 2 devices.
- Support external switching signals to trigger sequencer startup and shutdown.
- 2" colored LCD screen with Real - time showing of the voltage, date, time and the on/off date of each channel.

ACCESSORIES



- Ultra-compact headphone amplifier system for studio and stage applications.
- Phones level control per channel.
- USB bus powered, can be powered from power bank or any micro USB charger. Not to be charged from laptop or computer.

EMPTY DRUM PLATE

			
PED 320 4 4 HOLE	PED320-8 8 HOLE	PED320-12 12 HOLE	PED380M-8 8 HOLE
			
PED380M-12 HOLE	PED380M-16 HOLE	PED380M-20 HOLE	PED380M-24 HOLE
			
PED380P-8 8 HOLE	PED380P-12 HOLE	PED380P-16 HOLE	PED530M-20 HOLE
			
PED530M-24 HOLE	PED530M-32 HOLE	PED530M-40 HOLE	PED470M-12 HOLE
			
PED470M-16 HOLE	PED470M-20 HOLE	PED470M-24 HOLE	PED470M-32 HOLE
			
PED470M-40 HOLE			

HAWK®
TOTAL MUSIC SOLUTION

VIBE MINI 8BT

All-in-One Battery-Powered Portable PA
with Professional-Grade Mixer

MAKE SOME NOISE




2 YEAR MANUFACTURING WARRANTY AND 1 YEAR EXTENDED WARRANTY UPON REGISTRATION.

HAWK®
TOTAL MUSIC SOLUTION

NEW!
VIBE PRO+

SERIES
ACTIVE SPEAKER & SUBWOOFER



**POWER
THAT
MOVES THE
CROWD.**

2 YEAR MANUFACTURING WARRANTY AND 1 YEAR EXTENDED WARRANTY UPON REGISTRATION.



www.hawkpro.in



support@hawkpro.in



+91- 8130129200